

## MG LFP 24V Series

### - Technical specifications -

MGLFP24x230 (LFP 230Ah)

MGLFP24x280 (LFP 280Ah)

MGLFP24x304 (LFP 304Ah)



## Technical specifications

Technical specifications	MGLFP24x230 25.6 V / 230 Ah	MGLFP24x280 25.6 V / 280 Ah	MGLFP24x304 25.6 V / 304 Ah
Technology	Lithium-Ion next generation LiFePo4		
Cell configuration	8S1P		
Nominal voltage	25.6 V		
Nominal capacity	230 Ah	280 Ah	304 Ah
Nominal energy	5.8 kWh	7.2 kWh	7.8 kWh
Cycle Life DOD 80% <sup>1</sup>	> 3500	> 3500	> 4000
Specific energy <sup>2</sup>	143 Wh/kg	136 Wh/kg	145 Wh/kg
Weight	41 kg	53 kg	54 kg
<b>Discharge<sup>5</sup></b>			
Discharge cut-off voltage	24.0 V		
Recommended discharge current	< 115 A (< 0.5C)	< 140 A (< 0.5C)	< 152 A (< 0.5C)
Continuous discharge current	230 A (1.0 C)	280 A (1.0 C)	304 A (1.0 C)
Maximum discharge current <sup>3</sup>	345 A (1.5 C)	420 A (1.5 C)	456 A (1.5 C)
Fuses <sup>4</sup>	300A, fuse inside		
<b>Charge<sup>5</sup></b>			
Charge voltage	28.2 V		
Recommended charge current	< 115 A (< 0.5C)	< 140 A (< 0.5C)	< 152 A (< 0.5C)
Continuous charge current	230 A (1.0 C)	280 A (1.0 C)	304 A (1.0 C)
Maximum charge current (10 s) <sup>3</sup>	345 A (1.5 C)	280 A (1.0 C)	304 A (1.0 C)
<b>Configuration</b>			
Series configuration <sup>7</sup>	Up to 6 modules	Up to 6 modules	Up to 6 modules
Parallel configuration	Up to 96 modules.		
<b>Environmental</b>			
Operating temperature charge	0 to +45°C		
Operating temperature discharge	-20 to +55°C		
Recommended operating temperature	20 to +30°C		
Recommended storage temperature	10 to +35°C		
Humidity (non-condensing)	≤ 95 %		
<b>Mechanical</b>			
Power connections	M8 stud, 20 Nm		
IP-Protection class	IP30		
Cooling	Air, convection		
Dimensions ( l x h x w )	517 x 294 x 193 mm	652 x 294 x 193 mm	
<b>Safety</b>			
Battery Management System (BMS)	Integrated slave BMS		
Balancing	Passive		
Compatible BMS master controller	MG Master LV, MG Master HV		
Communication	CAN-Bus, RJ45 or M12 connection		
<b>Standards</b>			
EMC: Emission	EN-IEC 61000-6-3:2007/A1:2011/C11:2012		
EMC: Immunity	EN-IEC 61000-6-1:2007		
Low voltage directive	EN 60335-1:2012/AC:2014		
Approvals	IEC-EN62619, IEC-EN62620 (ES-TRIN <sup>6</sup> )		

This document is subject to changes without notification. All rights reserved. The information in this datasheet is carefully checked and is considered to be reliable, however MG Energy Systems assumes no responsibility for any inaccuracies.

## Footnotes

<sup>1</sup> End-of-Life is 70% of initial capacity at 25 °C. Cycle life is depending on the battery temperature. Higher battery temperature will result in a lower number of cycles.

<sup>2</sup> Including BMS and enclosure.

<sup>3</sup> Duration is depending on battery temperature.

<sup>4</sup> Fuses can be replaced with non-fused battery poles for high power and high voltage applications. In this case each battery string needs to be fused elsewhere in the circuit.

<sup>5</sup> Charge and discharge rates are depending on battery temperature and State-Of-Charge.

<sup>6</sup> In progress for 230 Ah and 304 Ah module.

<sup>7</sup> More than six in series on request.